

IN THE CLAIMS

Claims 1, 3-6, 8, 13 and 14 have been amended. New Claims 17-19 have been added.

1. (currently amended) A guidewire for penetrating into a vessel, comprising:

(a) an elongated wire assembly ~~for percutaneously or subcutaneously penetrating into a vessel and~~ capable of being guided to a designated region of a vessel within a patient's body, the elongated wire assembly comprising

a core section including a lumen disposed along a length of the core section, and an opening in the core section, the opening positioned so that the lumen is in fluid communication with the vessel; and

68 (b) a sensor ~~included with the elongated wire assembly~~ positioned within the lumen of the core section so that the sensor is in fluid communication with the vessel through the opening, the sensor being capable of ~~for~~ measuring the level of nitric oxide or superoxide molecules in a particular area ~~the vessel~~ of the patient's body.

2. (original) The guidewire of Claim 1, wherein the elongated wire assembly is configured to allow a catheter assembly to be slidably disposed over at least a portion thereof.

3. (currently amended) The guidewire of Claim 1, wherein the guidewire elongated wire assembly comprises a proximal section and a distal section, wherein the distal section is more flexible than the proximal section.

4. (currently amended) The guidewire of Claim 1, wherein the sensor comprises:

(a) a compound which can react with nitric oxide or superoxide such that subsequent to the reaction of the compound with nitric oxide or superoxide, the optical properties of the compound change; and

(b) an optical system ~~for~~capable of measuring the optical properties of the compound.

5. (currently amended) The guidewire of Claim 4, wherein the optical system includes a first fiber optic line ~~for~~capable of illuminating a light on the compound and a second fiber optic line to receive the light from the compound and to relay the received light to a detector.

6. (currently amended) The guidewire of Claim 1, wherein the sensor comprises:

(a) an electrically conductive substrate having an amperometric response that is substantially unaffected by the presence of nitric oxide or superoxide; and

(b) a coating ~~for~~capable of reacting with nitric oxide or superoxide so as to cause a change in the electrochemical potential of the nitric oxide or superoxide.

7. (original) The guidewire of Claim 1, wherein the sensor comprises a catalytic material capable of oxidizing nitric oxide or superoxide.

8. (currently amended) A diagnostic method for measuring the level of nitric oxide or superoxide in a vessel, comprising:

- as
- (a) positioning an elongated wire assembly into a vessel, the wire assembly including
 - a core section including a lumen disposed along a length of the core section,
 - an opening in the core section, the opening positioned so that the lumen is in fluid communication with the vessel, and
 - a sensor positioned within the lumen of the core section so that the sensor is in fluid communication with the vessel through the opening, the sensor being
 - capable of ~~for~~ measuring the level of nitric oxide or superoxide in the vessel;
 - (b) guiding the wire assembly to a designated region within the vessel; ~~and~~

(c) allowing body fluids to enter the lumen through the opening in the core section so that the body fluids are in contact with the sensor; and

(d) measuring the level of nitric oxide or superoxide in the region of the vessel of the body fluids in contact with the sensor.

9. (original) The method of Claim 8, wherein the vessel is a blood vessel.

10. (original) The method of Claim 8, further comprising inserting a catheter over the wire assembly to treat the region of the vessel.

11. (original) The method of Claim 8, additionally including delivering a stimulant to increase the production of nitric oxide or superoxide.

12. (original) The method of claim 11, wherein the stimulant comprises acetylcholine.

13. (currently amended) The method of Claim 8, wherein the sensor comprises:

28 (a) a compound which can react with nitric oxide or superoxide such that subsequent to the reaction of the compound with nitric oxide or superoxide, the optical properties of the compound change; and

(b) an optical system ~~for~~ capable of measuring the optical properties of the compound.

14. (currently amended) The method of Claim 8, wherein the sensor comprises:

(a) an electrically conductive substrate having an amperometric response that is substantially unaffected by the presence of nitric oxide or superoxide; and

(b) a coating ~~for~~ capable of reacting with nitric oxide or superoxide so as to cause a change in the electrochemical potential of the nitric oxide or superoxide.

15. (original) The method of Claim 8, wherein the sensor comprises a catalytic material capable of oxidizing nitric oxide or superoxide.

16. (original) The method of Claim 8, wherein the designated region within the vessel is affected by restenosis.

Please add the following New Claims:

17. (new) The guidewire of Claim 1, wherein the sensor includes a sensor tip capable of bending away from a central longitudinal axis of a distal end of the core section.

18. (new) The method of Claim 8, wherein the sensor includes a sensor tip capable of bending away from a central longitudinal axis of a distal end of the core section.

19. (new) A guidewire for penetrating into a vessel, comprising:

(a) an elongated wire assembly capable of being guided to a region of a vessel within a patient's body, the elongated wire assembly comprising a core section including a lumen disposed along a length of the core section; and

u8 (b) a sensor positioned within the lumen of the core section so that the sensor is in fluid communication with the vessel, the sensor being capable of measuring the level of nitric oxide or superoxide molecules in the vessel of the patient's body, wherein the sensor includes a sensor tip capable of bending away from a central longitudinal axis of a distal end of the core section.